



P 产品介绍

Product Introduction

GRT103-T
0.02mA)

6 4-20mA

4-20mA

(

S 性能参数

Specifications

| | | | | | |
|--|---------------------------------|------|--------|------|---------------|
| | 4 ~ 20mA | | | | |
| | 0.5%F.S | | | | |
| | 10-28VDC | | | | |
| | SWSN 433M 470M ; LORA 433M 470M | | | | |
| | 0.03mA | | | | |
| | SWSN | | | | |
| | SWSN | 1000 | 80-160 | LORA | 5000 500-1000 |
| | -30 ~ 80 , 95% | | | | |
| | 2~ 6 | | | | |
| | 145*90*40mm (| | | | |
| | DIN 35 | | | | |
| | 200g | | | | |

操作方法 Operation method

- 1) 4~20mA " 11" " 0" " G" " 0" " 12"
 " 1" " G" " 1" " 13" " 2" " G" " 2"
- 6
- 2) OFF ON ,

仪表设定 Instrument settings

- 1) " EN" 、 " ▶"
- " EN" 、 " ▲"
- 2) 按EN " " " "
- " EN" " EN" 、 " ▶"
- 3)
- 4)
- P004:
- P005:
- P006:
- P010: 1~255 30
- P014: 0-7

| U002 | U003 | U004 | U005 | U006 | U007 | U008 | U009 |
|------|------|------|------|------|------|------|------|
| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 |

0 4.1mA, U002 0.975, 3.9975 (4.1×0.975=3.9975) ,

| | | | |
|------|---|------|---|
| U010 | 0 | U018 | 4 |
| U011 | 0 | U019 | 4 |
| U012 | 1 | U020 | 5 |
| U013 | 1 | U021 | 5 |
| U014 | 2 | U022 | 6 |
| U015 | 2 | U023 | 6 |
| U016 | 3 | U024 | 7 |
| U017 | 3 | U025 | 7 |

安装与维护

Installation and maintenance

1)

2)

3)

4)